

容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流 +25℃(uA)	漏电流 +85℃(uA)	漏电流+125 ℃(uA)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)	ESR AT -55 ℃100Hz
6.3 Volt 额定电压 +85℃时 (4 Volt 额定电压 +125℃时)												
1	CA30-6.3V1uF(*)A	T3000A105(*)006(**)	(*)	6.3V1uF	A	1.00	8.00	8.00	6	6	6	1800
1.5	CA30-6.3V1.5uF(*)A	T3000A155(*)006(**)	(*)	6.3V1.5uF	A	1.00	8.00	8.00	6	6	6	1400
2.2	CA30-6.3V2.2uF(*)A	T3000A225(*)006(**)	(*)	6.3V2.2uF	A	1.00	8.00	8.00	6	6	6	1100
3.3	CA30-6.3V3.3uF(*)A	T3000A335(*)006(**)	(*)	6.3V3.3uF	A	1.00	8.00	8.00	6	6	6	700
4.7	CA30-6.3V4.7uF(*)A	T3000A475(*)006(**)	(*)	6.3V4.7uF	A	1.00	8.00	8.00	6	6	6	500
6.8	CA30-6.3V6.8uF(*)A	T3000A685(*)006(**)	(*)	6.3V6.8uF	A	1.00	8.00	8.00	8	8	8	350
10	CA30-6.3V10uF(*)A	T3000A106(*)006(**)	(*)	6.3V10uF	A	1.00	8.00	8.00	8	8	8	260
15	CA30-6.3V15uF(*)A	T3000A156(*)006(**)	(*)	6.3V15uF	A	1.00	8.00	8.00	10	10	10	200
22	CA30-6.3V22uF(*)A	T3000A226(*)006(**)	(*)	6.3V22uF	A	1.00	8.00	8.00	10	10	10	180
33	CA30-6.3V33uF(*)A	T3000A336(*)006(**)	(*)	6.3V33uF	A	1.00	8.00	8.00	12	12	12	125
47	CA30-6.3V47uF(*)A	T3000A476(*)006(**)	(*)	6.3V47uF	A	1.00	8.00	8.00	15	15	15	125
68	CA30-6.3V68uF(*)A	T3000A686(*)006(**)	(*)	6.3V68uF	A	1.00	8.00	8.00	18	18	18	125
100	CA30-6.3V100uF(*)A	T3000A107(*)006(**)	(*)	6.3V100uF	A	1.00	8.00	8.00	20	20	20	100
150	CA30-6.3V150uF(*)B	T3000B157(*)006(**)	(*)	6.3V150uF	B	1.00	8.00	8.00	30	30	30	80
220	CA30-6.3V220uF(*)B	T3000B227(*)006(**)	(*)	6.3V220uF	B	1.39	11.09	11.09	40	40	40	70
330	CA30-6.3V330uF(*)C	T3000C337(*)006(**)	(*)	6.3V330uF	C	2.08	16.63	16.63	40	40	40	60
470	CA30-6.3V470uF(*)C	T3000C477(*)006(**)	(*)	6.3V470uF	C	2.96	23.69	23.69	50	50	50	50
680	CA30-6.3V680uF(*)D	T3000D687(*)006(**)	(*)	6.3V680uF	D	4.28	34.27	34.27	50	50	50	35
1000	CA30-6.3V1000uF(*)D	T3000D108(*)006(**)	(*)	6.3V1000uF	D	6.30	50.40	50.40	60	60	60	25
1200	CA30-6.3V1200uF(*)E	T3000E128(*)006(**)	(*)	6.3V1200uF	E	7.56	60.48	60.48	60	60	60	25
1500	CA30-6.3V1500uF(*)E	T3000E158(*)006(**)	(*)	6.3V1500uF	E	9.45	75.60	75.60	60	60	60	20
2200	CA30-6.3V2200uF(*)F	T3000F228(*)006(**)	(*)	6.3V2200uF	F	13.86	110.88	110.88	70	70	70	20
3300	CA30-6.3V3300uF(*)G	T3000G338(*)006(**)	(*)	6.3V3300uF	G	20.79	166.32	166.32	80	80	80	15
10 Volt 额定电压 +85℃时 (6.3 Volt 额定电压 +125℃时)												
1	CA30-10V1uF(*)A	T3000A105(*)010(**)	(*)	10V1uF	A	1.00	8.00	8.00	6	6	6	1800
1.5	CA30-10V1.5uF(*)A	T3000A155(*)010(**)	(*)	10V1.5uF	A	1.00	8.00	8.00	6	6	6	1400
2.2	CA30-10V2.2uF(*)A	T3000A225(*)010(**)	(*)	10V2.2uF	A	1.00	8.00	8.00	6	6	6	1100
3.3	CA30-10V3.3uF(*)A	T3000A335(*)010(**)	(*)	10V3.3uF	A	1.00	8.00	8.00	6	6	6	700
4.7	CA30-10V4.7uF(*)A	T3000A475(*)010(**)	(*)	10V4.7uF	A	1.00	8.00	8.00	6	6	6	500
6.8	CA30-10V6.8uF(*)A	T3000A685(*)010(**)	(*)	10V6.8uF	A	1.00	8.00	8.00	8	8	8	350
10	CA30-10V10uF(*)A	T3000A106(*)010(**)	(*)	10V10uF	A	1.00	8.00	8.00	8	8	8	250
15	CA30-10V15uF(*)A	T3000A156(*)010(**)	(*)	10V15uF	A	1.00	8.00	8.00	10	10	10	200
22	CA30-10V22uF(*)A	T3000A226(*)010(**)	(*)	10V22uF	A	1.00	8.00	8.00	10	10	10	175
33	CA30-10V33uF(*)A	T3000A336(*)010(**)	(*)	10V33uF	A	1.00	8.00	8.00	12	12	12	125
47	CA30-10V47uF(*)A	T3000A476(*)010(**)	(*)	10V47uF	A	1.00	8.00	8.00	15	15	15	100
68	CA30-10V68uF(*)A	T3000A686(*)010(**)	(*)	10V68uF	A	1.00	8.00	8.00	18	18	18	80
100	CA30-10V100uF(*)A	T3000A107(*)010(**)	(*)	10V100uF	A	1.00	8.00	8.00	20	20	20	60
150	CA30-10V150uF(*)B	T3000B157(*)010(**)	(*)	10V150uF	B	1.50	12.00	12.00	30	30	30	55
220	CA30-10V220uF(*)C	T3000C227(*)010(**)	(*)	10V220uF	C	2.20	17.60	17.60	40	40	40	45
330	CA30-10V330uF(*)C	T3000C337(*)010(**)	(*)	10V330uF	C	3.30	26.40	26.40	45	45	45	40
470	CA30-10V470uF(*)D	T3000D477(*)010(**)	(*)	10V470uF	D	4.70	37.60	37.60	50	50	50	35
680	CA30-10V680uF(*)D	T3000D687(*)010(**)	(*)	10V680uF	D	6.80	54.40	54.40	50	50	50	30
1000	CA30-10V1000uF(*)E	T3000E108(*)010(**)	(*)	10V1000uF	E	10.00	80.00	80.00	50	50	50	25
1200	CA30-10V1200uF(*)E	T3000E128(*)010(**)	(*)	10V1200uF	E	12.00	96.00	96.00	60	60	60	25
1500	CA30-10V1500uF(*)F	T3000F158(*)010(**)	(*)	10V1500uF	F	15.00	120.00	120.00	60	60	60	20
2200	CA30-10V2200uF(*)G	T3000G228(*)010(**)	(*)	10V2200uF	G	22.00	176.00	176.00	70	70	70	20
3300	CA30-10V3300uF(*)H	T3000H338(*)010(**)	(*)	10V3300uF	H	33.00	264.00	264.00	80	80	80	15
16 Volt 额定电压 +85℃时 (10 Volt 额定电压 +125℃时)												
1	CA30-16V1uF(*)A	T3000A105(*)016(**)	(*)	16V1uF	A	1.00	8.00	8.00	6	6	6	1800
1.5	CA30-16V1.5uF(*)A	T3000A155(*)016(**)	(*)	16V1.5uF	A	1.00	8.00	8.00	6	6	6	1400
2.2	CA30-16V2.2uF(*)A	T3000A225(*)016(**)	(*)	16V2.2uF	A	1.00	8.00	8.00	6	6	6	1100
3.3	CA30-16V3.3uF(*)A	T3000A335(*)016(**)	(*)	16V3.3uF	A	1.00	8.00	8.00	6	6	6	700
4.7	CA30-16V4.7uF(*)A	T3000A475(*)016(**)	(*)	16V4.7uF	A	1.00	8.00	8.00	6	6	6	500
6.8	CA30-16V6.8uF(*)A	T3000A685(*)016(**)	(*)	16V6.8uF	A	1.00	8.00	8.00	8	8	8	350
10	CA30-16V10uF(*)A	T3000A106(*)016(**)	(*)	16V10uF	A	1.00	8.00	8.00	8	8	8	260
15	CA30-16V15uF(*)A	T3000A156(*)016(**)	(*)	16V15uF	A	1.00	8.00	8.00	10	10	10	180
22	CA30-16V22uF(*)A	T3000A226(*)016(**)	(*)	16V22uF	A	1.00	8.00	8.00	10	10	10	150
33	CA30-16V33uF(*)A	T3000A336(*)016(**)	(*)	16V33uF	A	1.00	8.00	8.00	12	12	12	110
47	CA30-16V47uF(*)A	T3000A476(*)016(**)	(*)	16V47uF	A	1.00	8.00	8.00	12	12	12	90
68	CA30-16V68uF(*)A	T3000A686(*)016(**)	(*)	16V68uF	A	1.09	8.70	8.70	18	18	18	80
100	CA30-16V100uF(*)B	T3000B107(*)016(**)	(*)	16V100uF	B	1.60	12.80	12.80	20	20	20	70
150	CA30-16V150uF(*)C	T3000C157(*)016(**)	(*)	16V150uF	C	2.40	19.20	19.20	30	30	30	60
220	CA30-16V220uF(*)C	T3000C227(*)016(**)	(*)	16V220uF	C	3.52	28.16	28.16	40	40	40	55
330	CA30-16V330uF(*)D	T3000D337(*)016(**)	(*)	16V330uF	D	5.28	42.24	42.24	40	40	40	45
470	CA30-16V470uF(*)E	T3000E477(*)016(**)	(*)	16V470uF	E	7.52	60.16	60.16	40	40	40	40
680	CA30-16V680uF(*)F	T3000F687(*)016(**)	(*)	16V680uF	F	10.88	87.04	87.04	45	45	45	35
1000	CA30-16V1000uF(*)G	T3000G108(*)016(**)	(*)	16V1000uF	G	16.00	128.00	128.00	50	50	50	30
1200	CA30-16V1200uF(*)G	T3000G128(*)016(**)	(*)	16V1200uF	G	19.20	153.60	153.60	50	50	50	25
1500	CA30-16V1500uF(*)H	T3000H158(*)016(**)	(*)	16V1500uF	H	24.00	192.00	192.00	60	60	60	20
2200	CA30-16V2200uF(*)I	T3000I228(*)016(**)	(*)	16V2200uF	I	35.20	281.60	281.60	70	70	70	20
25 Volt 额定电压 +85℃时 (16 Volt 额定电压 +125℃时)												
1	CA30-25V1uF(*)A	T3000A105(*)025(**)	(*)	25V1uF	A	1.00	8.00	8.00	6	6	6	1800

容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流 +25℃(uA)	漏电流 +85℃(uA)	漏电流+125 ℃(uA)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)	ESR AT -55 ℃100Hz
1.5	CA30-25V1.5uF(*)A	T3000A155(*)025(**)	(*)	25V1.5uF	A	1.00	8.00	8.00	6	6	6	1400
2.2	CA30-25V2.2uF(*)A	T3000A225(*)025(**)	(*)	25V2.2uF	A	1.00	8.00	8.00	6	6	6	1100
3.3	CA30-25V3.3uF(*)A	T3000A335(*)025(**)	(*)	25V3.3uF	A	1.00	8.00	8.00	6	6	6	700
4.7	CA30-25V4.7uF(*)A	T3000A475(*)025(**)	(*)	25V4.7uF	A	1.00	8.00	8.00	6	6	6	500
6.8	CA30-25V6.8uF(*)A	T3000A685(*)025(**)	(*)	25V6.8uF	A	1.00	8.00	8.00	8	8	8	300
10	CA30-25V10uF(*)A	T3000A106(*)025(**)	(*)	25V10uF	A	1.00	8.00	8.00	8	8	8	260
15	CA30-25V15uF(*)A	T3000A156(*)025(**)	(*)	25V15uF	A	1.00	8.00	8.00	10	10	10	175
22	CA30-25V22uF(*)A	T3000A226(*)025(**)	(*)	25V22uF	A	1.00	8.00	8.00	10	10	10	150
33	CA30-25V33uF(*)A	T3000A336(*)025(**)	(*)	25V33uF	A	1.00	8.00	8.00	12	12	12	110
47	CA30-25V47uF(*)A	T3000A476(*)025(**)	(*)	25V47uF	A	1.18	9.40	9.40	12	12	12	80
68	CA30-25V68uF(*)B	T3000B686(*)025(**)	(*)	25V68uF	B	1.70	13.60	13.60	20	20	20	75
100	CA30-25V100uF(*)C	T3000C107(*)025(**)	(*)	25V100uF	C	2.50	20.00	20.00	20	20	20	70
150	CA30-25V150uF(*)D	T3000D157(*)025(**)	(*)	25V150uF	D	3.75	30.00	30.00	25	25	25	60
220	CA30-25V220uF(*)D	T3000D227(*)025(**)	(*)	25V220uF	D	5.50	44.00	44.00	30	30	30	55
330	CA30-25V330uF(*)E	T3000E337(*)025(**)	(*)	25V330uF	E	8.25	66.00	66.00	30	30	30	45
470	CA30-25V470uF(*)F	T3000F477(*)025(**)	(*)	25V470uF	F	11.75	94.00	94.00	40	40	40	40
680	CA30-25V680uF(*)G	T3000G687(*)025(**)	(*)	25V680uF	G	17.00	136.00	136.00	35	35	35	35
1000	CA30-25V1000uF(*)H	T3000H108(*)025(**)	(*)	25V1000uF	H	25.00	200.00	200.00	40	40	40	30
1200	CA30-25V1200uF(*)H	T3000H128(*)025(**)	(*)	25V1200uF	H	30.00	240.00	240.00	50	50	50	25
1500	CA30-25V1500uF(*)I	T3000I158(*)025(**)	(*)	25V1500uF	I	37.50	300.00	300.00	60	60	60	20
40 Volt 额定电压 +85℃时 (25 Volt 额定电压 +125℃时)												
1	CA30-40V1uF(*)A	T3000A105(*)040(**)	(*)	40V1uF	A	1.00	8.00	8.00	6	6	6	1800
1.5	CA30-40V1.5uF(*)A	T3000A155(*)040(**)	(*)	40V1.5uF	A	1.00	8.00	8.00	6	6	6	1400
2.2	CA30-40V2.2uF(*)A	T3000A225(*)040(**)	(*)	40V2.2uF	A	1.00	8.00	8.00	6	6	6	1100
3.3	CA30-40V3.3uF(*)A	T3000A335(*)040(**)	(*)	40V3.3uF	A	1.00	8.00	8.00	6	6	6	700
4.7	CA30-40V4.7uF(*)A	T3000A475(*)040(**)	(*)	40V4.7uF	A	1.00	8.00	8.00	6	6	6	450
6.8	CA30-40V6.8uF(*)A	T3000A685(*)040(**)	(*)	40V6.8uF	A	1.00	8.00	8.00	8	8	8	350
10	CA30-40V10uF(*)A	T3000A106(*)040(**)	(*)	40V10uF	A	1.00	8.00	8.00	8	8	8	260
15	CA30-40V15uF(*)A	T3000A156(*)040(**)	(*)	40V15uF	A	1.00	8.00	8.00	10	10	10	175
22	CA30-40V22uF(*)A	T3000A226(*)040(**)	(*)	40V22uF	A	1.00	8.00	8.00	12	12	12	145
33	CA30-40V33uF(*)B	T3000B336(*)040(**)	(*)	40V33uF	B	1.32	10.56	10.56	12	12	12	110
47	CA30-40V47uF(*)C	T3000C476(*)040(**)	(*)	40V47uF	C	1.88	15.04	15.04	15	15	15	80
68	CA30-40V68uF(*)C	T3000C686(*)040(**)	(*)	40V68uF	C	2.72	21.76	21.76	15	15	15	75
100	CA30-40V100uF(*)C	T3000C107(*)040(**)	(*)	40V100uF	C	4.00	32.00	32.00	20	20	20	65
150	CA30-40V150uF(*)D	T3000D157(*)040(**)	(*)	40V150uF	D	6.00	48.00	48.00	20	20	20	50
220	CA30-40V220uF(*)E	T3000E227(*)040(**)	(*)	40V220uF	E	8.80	70.40	70.40	25	25	25	45
330	CA30-40V330uF(*)F	T3000F337(*)040(**)	(*)	40V330uF	F	13.20	105.60	105.60	25	25	25	35
470	CA30-40V470uF(*)F	T3000F477(*)040(**)	(*)	40V470uF	F	18.80	150.40	150.40	30	30	30	35
680	CA30-40V680uF(*)G	T3000G687(*)040(**)	(*)	40V680uF	G	27.20	217.60	217.60	40	40	40	30
1000	CA30-40V1000uF(*)H	T3000H108(*)040(**)	(*)	40V1000uF	H	40.00	320.00	320.00	45	45	45	30
1200	CA30-40V1200uF(*)I	T3000I128(*)040(**)	(*)	40V1200uF	I	48.00	384.00	384.00	50	50	50	25
50 Volt 额定电压 +85℃时 (30 Volt 额定电压 +125℃时)												
1	CA30-50V1uF(*)A	T3000A105(*)050(**)	(*)	50V1uF	A	1.00	8.00	8.00	6	6	6	1800
1.5	CA30-50V1.5uF(*)A	T3000A155(*)050(**)	(*)	50V1.5uF	A	1.00	8.00	8.00	6	6	6	1400
2.2	CA30-50V2.2uF(*)A	T3000A225(*)050(**)	(*)	50V2.2uF	A	1.00	8.00	8.00	6	6	6	1100
3.3	CA30-50V3.3uF(*)A	T3000A335(*)050(**)	(*)	50V3.3uF	A	1.00	8.00	8.00	6	6	6	700
4.7	CA30-50V4.7uF(*)A	T3000A475(*)050(**)	(*)	50V4.7uF	A	1.00	8.00	8.00	6	6	6	500
6.8	CA30-50V6.8uF(*)A	T3000A685(*)050(**)	(*)	50V6.8uF	A	1.00	8.00	8.00	8	8	8	350
10	CA30-50V10uF(*)A	T3000A106(*)050(**)	(*)	50V10uF	A	1.00	8.00	8.00	8	8	8	260
15	CA30-50V15uF(*)A	T3000A156(*)050(**)	(*)	50V15uF	A	1.00	8.00	8.00	10	10	10	175
22	CA30-50V22uF(*)B	T3000B226(*)050(**)	(*)	50V22uF	B	1.10	8.80	8.80	12	12	12	150
33	CA30-50V33uF(*)C	T3000C336(*)050(**)	(*)	50V33uF	C	1.65	13.20	13.20	12	12	12	110
47	CA30-50V47uF(*)C	T3000C476(*)050(**)	(*)	50V47uF	C	2.35	18.80	18.80	15	15	15	80
68	CA30-50V68uF(*)D	T3000D686(*)050(**)	(*)	50V68uF	D	3.40	27.20	27.20	15	15	15	75
100	CA30-50V100uF(*)D	T3000D107(*)050(**)	(*)	50V100uF	D	5.00	40.00	40.00	20	20	20	65
150	CA30-50V150uF(*)E	T3000E157(*)050(**)	(*)	50V150uF	E	7.50	60.00	60.00	20	20	20	50
220	CA30-50V220uF(*)E	T3000E227(*)050(**)	(*)	50V220uF	E	11.00	88.00	88.00	25	25	25	45
330	CA30-50V330uF(*)F	T3000F337(*)050(**)	(*)	50V330uF	F	16.50	132.00	132.00	25	25	25	45
470	CA30-50V470uF(*)G	T3000G477(*)050(**)	(*)	50V470uF	G	23.50	188.00	188.00	35	35	35	35
680	CA30-50V680uF(*)H	T3000H687(*)050(**)	(*)	50V680uF	H	34.00	272.00	272.00	40	40	40	35
1000	CA30-50V1000uF(*)I	T3000I108(*)050(**)	(*)	50V1000uF	I	50.00	400.00	400.00	50	50	50	30
63 Volt 额定电压 +85℃时 (40 Volt 额定电压 +125℃时)												
1	CA30-63V1uF(*)A	T3000A105(*)063(**)	(*)	63V1uF	A	1.00	8.00	8.00	6	6	6	1800
1.5	CA30-63V1.5uF(*)A	T3000A155(*)063(**)	(*)	63V1.5uF	A	1.00	8.00	8.00	6	6	6	1400
2.2	CA30-63V2.2uF(*)A	T3000A225(*)063(**)	(*)	63V2.2uF	A	1.00	8.00	8.00	6	6	6	1100
3.3	CA30-63V3.3uF(*)A	T3000A335(*)063(**)	(*)	63V3.3uF	A	1.00	8.00	8.00	6	6	6	700
4.7	CA30-63V4.7uF(*)A	T3000A475(*)063(**)	(*)	63V4.7uF	A	1.00	8.00	8.00	6	6	6	500
6.8	CA30-63V6.8uF(*)A	T3000A685(*)063(**)	(*)	63V6.8uF	A	1.00	8.00	8.00	8	8	8	350
10	CA30-63V10uF(*)A	T3000A106(*)063(**)	(*)	63V10uF	A	1.00	8.00	8.00	8	8	8	260
15	CA30-63V15uF(*)B	T3000B156(*)063(**)	(*)	63V15uF	B	1.00	8.00	8.00	10	10	10	175
22	CA30-63V22uF(*)C	T3000C226(*)063(**)	(*)	63V22uF	C	1.39	11.09	11.09	12	12	12	140
33	CA30-63V33uF(*)C	T3000C336(*)063(**)	(*)	63V33uF	C	2.08	16.63	16.63	12	12	12	100
47	CA30-63V47uF(*)C	T3000C476(*)063(**)	(*)	63V47uF	C	2.96	23.69	23.69	15	15	15	80

容量 (uF)	聚电料号	ADMAT料号	容量偏差	规格	壳号	漏电流 +25℃(uA)	漏电流 +85℃(uA)	漏电流+125 ℃(uA)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)	ESR AT -55 ℃100Hz
68	CA30-63V68uF(*)D	T3000D686(*)063(**)	(*)	63V68uF	D	4.28	34.27	34.27	15	15	15	65
100	CA30-63V100uF(*)D	T3000D107(*)063(**)	(*)	63V100uF	D	6.30	50.40	50.40	20	20	20	60
150	CA30-63V150uF(*)E	T3000E157(*)063(**)	(*)	63V150uF	E	9.45	75.60	75.60	20	20	20	50
220	CA30-63V220uF(*)F	T3000F227(*)063(**)	(*)	63V220uF	F	13.86	110.88	110.88	25	25	25	45
330	CA30-63V330uF(*)G	T3000G337(*)063(**)	(*)	63V330uF	G	20.79	166.32	166.32	25	25	25	35
470	CA30-63V470uF(*)H	T3000H477(*)063(**)	(*)	63V470uF	H	29.61	236.88	236.88	40	40	40	30
680	CA30-63V680uF(*)I	T3000I687(*)063(**)	(*)	63V680uF	I	42.84	342.72	342.72	40	40	40	30
75 Volt 额定电压 +85℃时 (50 Volt 额定电压 +125℃时)												
1	CA30-75V1uF(*)A	T3000A105(*)075(**)	(*)	75V1uF	A	1.00	8.00	8.00	6	6	6	1800
1.5	CA30-75V1.5uF(*)A	T3000A155(*)075(**)	(*)	75V1.5uF	A	1.00	8.00	8.00	6	6	6	1400
2.2	CA30-75V2.2uF(*)A	T3000A225(*)075(**)	(*)	75V2.2uF	A	1.00	8.00	8.00	6	6	6	1100
3.3	CA30-75V3.3uF(*)A	T3000A335(*)075(**)	(*)	75V3.3uF	A	1.00	8.00	8.00	6	6	6	700
4.7	CA30-75V4.7uF(*)A	T3000A475(*)075(**)	(*)	75V4.7uF	A	1.00	8.00	8.00	6	6	6	500
6.8	CA30-75V6.8uF(*)B	T3000B685(*)075(**)	(*)	75V6.8uF	B	1.00	8.00	8.00	8	8	8	350
10	CA30-75V10uF(*)B	T3000B106(*)075(**)	(*)	75V10uF	B	1.00	8.00	8.00	8	8	8	260
15	CA30-75V15uF(*)C	T3000C156(*)075(**)	(*)	75V15uF	C	1.13	9.00	9.00	10	10	10	175
22	CA30-75V22uF(*)C	T3000C226(*)075(**)	(*)	75V22uF	C	1.65	13.20	13.20	12	12	12	150
33	CA30-75V33uF(*)D	T3000D336(*)075(**)	(*)	75V33uF	D	2.48	19.80	19.80	12	12	12	110
47	CA30-75V47uF(*)D	T3000D476(*)075(**)	(*)	75V47uF	D	3.53	28.20	28.20	15	15	15	80
68	CA30-75V68uF(*)E	T3000E686(*)075(**)	(*)	75V68uF	E	5.10	40.80	40.80	15	15	15	70
100	CA30-75V100uF(*)E	T3000E107(*)075(**)	(*)	75V100uF	E	7.50	60.00	60.00	20	20	20	60
150	CA30-75V150uF(*)F	T3000F157(*)075(**)	(*)	75V150uF	F	11.25	90.00	90.00	20	20	20	50
220	CA30-75V220uF(*)G	T3000G227(*)075(**)	(*)	75V220uF	G	16.50	132.00	132.00	25	25	25	45
330	CA30-75V330uF(*)H	T3000H337(*)075(**)	(*)	75V330uF	H	24.75	198.00	198.00	25	25	25	35
100 Volt 额定电压 +85℃时 (63 Volt 额定电压 +125℃时)												
1	CA30-100V1uF(*)A	T3000A105(*)100(**)	(*)	100V1uF	A	1.00	8.00	8.00	6	6	6	1800
1.5	CA30-100V1.5uF(*)A	T3000A155(*)100(**)	(*)	100V1.5uF	A	1.00	8.00	8.00	6	6	6	1400
2.2	CA30-100V2.2uF(*)A	T3000A225(*)100(**)	(*)	100V2.2uF	A	1.00	8.00	8.00	6	6	6	1100
3.3	CA30-100V3.3uF(*)A	T3000A335(*)100(**)	(*)	100V3.3uF	A	1.00	8.00	8.00	6	6	6	700
4.7	CA30-100V4.7uF(*)A	T3000A475(*)100(**)	(*)	100V4.7uF	A	1.00	8.00	8.00	6	6	6	500
6.8	CA30-100V6.8uF(*)B	T3000B685(*)100(**)	(*)	100V6.8uF	B	1.00	8.00	8.00	8	8	8	350
10	CA30-100V10uF(*)B	T3000B106(*)100(**)	(*)	100V10uF	B	1.00	8.00	8.00	8	8	8	260
15	CA30-100V15uF(*)C	T3000C156(*)100(**)	(*)	100V15uF	C	1.50	12.00	12.00	10	10	10	175
22	CA30-100V22uF(*)C	T3000C226(*)100(**)	(*)	100V22uF	C	2.20	17.60	17.60	10	10	10	150
33	CA30-100V33uF(*)D	T3000D336(*)100(**)	(*)	100V33uF	D	3.30	26.40	26.40	15	15	15	100
47	CA30-100V47uF(*)E	T3000E476(*)100(**)	(*)	100V47uF	E	4.70	37.60	37.60	15	15	15	70
68	CA30-100V68uF(*)E	T3000E686(*)100(**)	(*)	100V68uF	E	6.80	54.40	54.40	15	15	15	65
100	CA30-100V100uF(*)F	T3000F107(*)100(**)	(*)	100V100uF	F	10.00	80.00	80.00	20	20	20	60
150	CA30-100V150uF(*)G	T3000G157(*)100(**)	(*)	100V150uF	G	15.00	120.00	120.00	20	20	20	50
220	CA30-100V220uF(*)H	T3000H227(*)100(**)	(*)	100V220uF	H	22.00	176.00	176.00	20	20	20	45
330	CA30-100V330uF(*)I	T3000I337(*)100(**)	(*)	100V330uF	I	33.00	264.00	264.00	25	25	25	35
125 Volt 额定电压 +85℃时 (75 Volt 额定电压 +125℃时)												
0.47	CA30-125V0.47uF(*)A	T3000A474(*)125(**)	(*)	125V0.47uF	A	1.00	8.00	8.00	6	6	6	4500
0.68	CA30-125V0.68uF(*)A	T3000A684(*)125(**)	(*)	125V0.68uF	A	1.00	8.00	8.00	6	6	6	3000
1	CA30-125V1uF(*)A	T3000A105(*)125(**)	(*)	125V1uF	A	1.00	8.00	8.00	6	6	6	1800
1.5	CA30-125V1.5uF(*)A	T3000A155(*)125(**)	(*)	125V1.5uF	A	1.00	8.00	8.00	6	6	6	1400
2.2	CA30-125V2.2uF(*)A	T3000A225(*)125(**)	(*)	125V2.2uF	A	1.00	8.00	8.00	6	6	6	1100
3.3	CA30-125V3.3uF(*)A	T3000A335(*)125(**)	(*)	125V3.3uF	A	1.00	8.00	8.00	6	6	6	700
4.7	CA30-125V4.7uF(*)B	T3000B475(*)125(**)	(*)	125V4.7uF	B	1.00	8.00	8.00	6	6	6	500
6.8	CA30-125V6.8uF(*)B	T3000B685(*)125(**)	(*)	125V6.8uF	B	1.00	8.00	8.00	8	8	8	350
10	CA30-125V10uF(*)C	T3000C106(*)125(**)	(*)	125V10uF	C	1.25	10.00	10.00	10	10	10	260
15	CA30-125V15uF(*)C	T3000C156(*)125(**)	(*)	125V15uF	C	1.88	15.00	15.00	10	10	10	175
22	CA30-125V22uF(*)D	T3000D226(*)125(**)	(*)	125V22uF	D	2.75	22.00	22.00	15	15	15	150
33	CA30-125V33uF(*)D	T3000D336(*)125(**)	(*)	125V33uF	D	4.13	33.00	33.00	15	15	15	120
47	CA30-125V47uF(*)E	T3000E476(*)125(**)	(*)	125V47uF	E	5.88	47.00	47.00	15	15	15	90
68	CA30-125V68uF(*)G	T3000F686(*)125(**)	(*)	125V68uF	F	8.50	68.00	68.00	15	15	15	70
100	CA30-125V100uF(*)G	T3000G107(*)125(**)	(*)	125V100uF	G	12.50	100.00	100.00	15	15	15	50
150	CA30-125V150uF(*)H	T3000H157(*)125(**)	(*)	125V150uF	H	18.75	150.00	150.00	20	20	20	45

(*)：电容量允许偏差：±10%，±20%

如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。